



VpCI® ADDITIVES FOR COATINGS, FLUIDS, ADHESIVES AND PLASTICS

VpCI Coolant Antifreeze



PRODUCT DESCRIPTION

VpCI Coolant Antifreeze is a corrosion inhibiting heat transfer fluid featuring the wide range of use temperatures. This fluid is specifically formulated with inhibitor package to offer thermostability and vapor phase multimetal corrosion protection. The range of working temperature is from -60F (-50 C) to 280 F (140C), depending on dilution rate with water.

FEATURES

- Protects ferrous and non-ferrous metals from corrosion and pitting
- Nitrite, chromate, and heavy metal silicate free
- Contains contact and vapor phase corrosion inhibitors
- Economical
- Environmentally acceptable
- Thermally stable over a wide range of temperatures

PHYSICAL PROPERTIES

Appearance	Clear yellow liquid
pH	8.0-9.0 (50% in water)
Non-volatile Content	95-99%
Solubility in Water	100%
Density	9.4-9.5 lb/gal(1.13-1.14 kg/l)
Reserved alkalinity	15-17 ml

TEST DATA

ASTM D-1384-87 (Standard Test Method for Engine Coolant in Glassware) for engine antifreeze/coolants.

Weight Loss per Specimen (mg)

	Copper	Brass	Solder
33% VpCI Coolant Antifreeze in corrosive water	6-8	1-2	8-9
ASTM D-3306 Requirements	≤10	≤10	≤30
GM 1899 M Requirements	≤10	≤10	≤20
GM 1825 M Requirements	≤10	≤10	≤20

	Carbon Steel	Cast Iron	Aluminum
33% VpCI Coolant Antifreeze in corrosive water	1-2	6-10	8-12
ASTM D-3306 Requirements	≤10	≤10	≤30
GM 1899 M Requirements	≤10	≤10	≤20
GM 1825 M Requirements	≤10	≤10	≤20



TYPICAL APPLICATIONS

Thermally demanding application and where long fluid life and extended maintenance intervals are desired. Also, suitable for single fluid process heating and cooling. VpCI Coolant Antifreeze can be diluted with deionized or distilled water according to the required working temperature range.

Contact Cortec for more information and assistance.

PACKAGING AND STORAGE

VpCI Coolant Antifreeze is packaged in 5 gallon (19 liter) plastic pails, 55 gallon (208 liter) steel drums, liquid totes and bulk. It should be stored in a tightly closed container. The shelf life is 24 months.

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

printed on recycled paper  10% post consumer

Revised 12/9/04. Cortec Corporation 2004. Supersedes: 12/2/04.

