



## HIGH PERFORMANCE VpCI® PACKAGING

# Cor-Pak® EcoWeave® VpCI® Woven Polyethylene, Patented



### DESCRIPTION

Cor-Pak® EcoWeave® is a woven polyethylene film that offers extra strength, durability, multimetal corrosion protection, reusability and recyclability. Cor-Pak® EcoWeave® is the new solution for tough corrosion packaging problems. From raw materials to finished product, Cor-Pak® EcoWeave® will provide the protection you need for expensive, but heavy, raw materials and finished products. It provides protection against corrosion, mother nature and traditional transit and storage damage.

Use Cor-Pak® EcoWeave® for:

- Export packaging of expensive and larger equipment
- Steel sheeting and flat stock
- Steel coils
- Pallet shrouds
- Heavy equipment covers
- Heavy metal parts
- Equipment and product pouches

The real cost of packaging is the cost of the product if it's not protected from corrosion and transit damage.

Cor-Pak® EcoWeave® is the answer:

- It can be custom sewn for an exact fit
- It can be wrapped around a finished product or skid of raw materials
- It's reusable over and over

### ADVANTAGES

Cor-Pak® EcoWeave® offers strength, tear resistance, durability and protection from corrosion. Many packaging applications require a tear resistant shroud to accommodate the sharp edges of equipment or steel coil during shipment. The woven structure of Cor-Pak® EcoWeave® will help prevent damage to the shroud, thus preserving the integrity of the VpCI® protection and preventing corrosion from occurring.

Woven polyethylene is a durable, but lightweight material for all your demanding projects. It utilizes a high density polyethylene scrim as its base material and is then extrusion coated with VpCI®-126 to give it strength and the proven corrosion protection of Cortec® VpCI® film technology.

### MULTIMETAL PROTECTION

Metal parts packaged in Cor-Pak® EcoWeave® receive continuous protection against salt environments, excessive humidity, condensation, moisture, aggressive industrial atmospheres and dissimilar metal corrosion. The VpCIs vaporize and then condense on all metal surfaces in an enclosed package. Cor-Pak® EcoWeave® offers complete product protection during storage, as well as domestic and overseas shipments, virtually eliminating any rust claims. Cor-Pak® EcoWeave® can be custom manufactured in heavier weights to suit all shipping or storage requirements.



**CORTEC**  
CORPORATION

Environmentally Safe VpCI®/MCI® Technologies

**PHYSICAL PROPERTIES**

Property	Unit	Values	Test Method
Unit Weight	oz/yd <sup>2</sup> (g/m <sup>2</sup> )	3.3 (112)	ASTM D3775
Tensile Grab Strength	1 bf (N)	Warp 115 (506)	ASTM D1682-64
		Weft 80 (352)	
Tear Strength	1 bf (N)	Warp 41 (180)	ASTM D2261-71
		Weft 41 (180)	
Width	In (cm)	Up to 144 (366)	

**METALS PROTECTED**

- Carbon Steel
- Galvanized Steel
- Stainless Steel
- Aluminum
- Brass
- Copper
- Solder
- Silver

**VAPOR INHIBITING ABILITY TEST per MIL-B-22019C**

Cor-Pak EcoWeave	Pass	No corrosion
<b>Control</b>	Fail	Corrosion

**ACCELERATED CORROSION TEST**

Wrapped panels exposed to a SO <sub>2</sub> (sulfur dioxide) environment for 24 hours		
Cor-Pak EcoWeave	Pass	No Corrosion
<b>Control</b>	Fail	Corrosion

**PACKAGING AND STORAGE**

Available in standard and custom sizes.  
Contact Cortec Customer Service for inquiries and custom requirements.

**FOR INDUSTRIAL USE ONLY**

**KEEP OUT OF REACH OF CHILDREN**

**KEEP CONTAINER TIGHTLY CLOSED**

**NOT FOR INTERNAL CONSUMPTION**

**CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION**

**LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

**BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.** No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

**THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.**



4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com  
Internet <http://www.CortecVpCI.com>

printed on recycled paper 10% post consumer

Revised 8/26/03. Cortec Corporation 1997-2003. All rights reserved. Supersedes: 9/97. Cor-Pak® and VpCI® are trademarks of Cortec Corporation

Distributed by:



**OTiK Sp. z o.o.**

ul. Hutnicza 4  
81-061 Gdynia  
tel.: 58 6230498  
fax: 58 6230496

[otik@use.pl](mailto:otik@use.pl)  
[www.inhibitory.use.pl](http://www.inhibitory.use.pl)



Certificate No.70781

Certificate No.81867