



SURFACE PREPARATION PRODUCTS

VCI-411 Gel

DESCRIPTION

VCI-411 Gel is a D-Limonene-based cleaner and degreaser. It is designed to remove heavy oils and greases from vertical surfaces and hard to reach areas.

VCI-411 Gel can be used on all engineering metals and alloys. It can be used to clean engines, shop walls and ceilings, bridge decking and removal of waxy temporary coatings such as Cortec® VCI-368 and VCI-389.

TYPICAL USES

- Engines coated with grease or oil deposits
- Machined parts coated with waxes or greases prior to assembly
- Castings coated with temporary protective oils or temporary wax coatings
- Excellent for removing adhesives
- Drilling pipes and tools contaminated with crude oils and deposits
- Tanks, vessels, valves and heat exchangers with heavy hydrocarbon and scale deposits

ADVANTAGES

- Safe to handle
- Pleasant odor
- Biodegradable
- Effective for hard-to-reach areas

APPLICATION

VCI-411 Gel is a ready-to-use product. Can be applied by brush, spray or roller.

PROPERTIES

Appearance	Clear yellow gel
Flash Point	134°F (57°C)
Odor	Mild
pH	9.0 - 10.5
Viscosity	>100,000 cps
Density	8.0 - 8.1 lb/gal (0.96-0.97 kg/l)

PACKAGING AND STORAGE

VCI-411 Gel is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes and bulk.

Minimum storage temperature: 32°F (0°C)

Maximum storage temperature: 120°F (49°C)

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

Distributed by:



OTiK Sp. z o.o.
ul. Hutnicza 4
81-061 Gdynia
tel.: 58 6230498
fax: 58 6230496
otik@use.pl
www.inhibitory.use.pl

printed on recycled paper  10% post consumer

Revised 7/11/00. Cortec Corporation 2000. All rights reserved. Supersedes: 1/28/00.



Certificate No. 43345